Masporti Heating

ADENA





- · Heats small to medium sized areas
- Efficiently heats areas up to 162m²
- 6mm steel firebox for durability
- Radiant 6mm cooktop
- Lined with ceramic fire bricks and a steel baffle for efficient burning

MODEL	981902
FINISH	VHT Black
FIREBOX	Steel
EST. PEAK OUTPUT	16.2kW
APPROX. HEAT AREA	162m ²
EMISSIONS	1.0g/kg
EFFICIENCY	60.0%
DIMENSIONS (WxDxH)	481 x 536 x 1025mm
FIREBOX DIMENSIONS (WxDxH)	265 x 325 x 410mm
LOG SIZE	290mm





Minimum distance to heat sensitive materials (mm) when a flue deflector is fitter, and floor protector sizes as per standard AS/NZS 2918:2001.

FLUE SHIELD	Α	В	C	D	Е	F	G	Н	- 1	J	K	L	M	Ν	R	W
FUF	425	625	300	117	450	586	866	679	415	715	1245	1619	1291	659	960	482
FDR	250	500	300	117	320	411	741	549	415	715	1070	1435	1161	659	776	482
AGA	250	650	300	117	350	411	891	579	415	715	1070	1478	1191	659	819	482

FUF: Flomet Universal Flue system with full length decorative heat shield.

FDR: Flomet Dropbox with Single Skin Reflective Shield.

AGA: Acom/Air Group Special Insulated Flue System





