

OTHER FEATURES

FIREPLACE MODEL	NOMINAL MAXIMUM GAS CONSUMPTION			OUTPUT		
	NG	PROPANE	ULPG	NG	PROPANE	UPLG
GF1500LST	50 MJ/hr	49 MJ/hr	44 MJ/hr	10.2 kW	10 kW	9 kW
GF1500L	50 MJ/hr	49 MJ/hr	44 MJ/hr	10.8 kW	10.7 kW	9.7 kW
GF950L	35 MJ/hr	28 MJ/hr	28 MJ/hr	7.8 kW	6.3 kW	6.4 kW
GF900C	32 MJ/hr	28 MJ/hr	28 MJ/hr	6.9kW	6 kW	6 kW

NOTE : kW output based on horizontal flue run.

DESIGN OPTIONS



Clean edge finish (no fascia)



Door frame and fascia in black



Door frame and 22mm finishing trim in black



Glass fascia in black with black inner door frame



Glass fascia in black with brushed stainless steel inner door frame



Door frame and fascia in brushed stainless steel

FINISHES




Clean Front with 22mm Finishing Trim



Black Fascia



Brushed Stainless Steel Fascia



Black Glass Fascia

FASCIA DIMENSIONS (mm)	GF1500LST		GF1500L		GF950L	
	WIDTH	HEIGHT	WIDTH	HEIGHT	WIDTH	HEIGHT
Clean edge finish option (no fascia)	1267	459	1267	459	1000	450
22mm finishing trim	1300	495	1300	495	1035	480
Door frame and fascia in black	1359	549	1359	549	1091	540
Door frame and fascia in brushed stainless steel	1359	549	1359	549	1091	540
Glass fascia in black or with brushed stainless steel inner door frame	1460	654	1460	654	1192	641